



MILK TANK PLAN CHECK GUIDE

DAIRY NAME/PATRON #: _____ ADDRESS: _____ PHONE: _____

CONTRACTOR: _____ PHONE: _____

CODE	REQUIREMENTS	YES	NO	COMMENTS
480.7 (a)	1. Two copies of plans with scaled dimensions for each installation are required.			
480.7 (b)	2. Tank must be installed at least two (2) feet from all walls of the milk room on all sides.			
480.7 (b)	3. A clearance of at least (6) inches must be provided between the bottom of the tank or pipe under tank and floor.			
480.7(b)	4. The tank must not be located over a floor drain.			
648 (a)	5. The minimum distance between a farm tank and the wash trays shall be five (5) feet.			
648 (d){2}	6. Tank must not be closer than two (2) feet from the milk house ceiling			
480.7 (c)	7. Farm tanks must be provided with accurate thermometers			
480.75 (a) (1)	8. Farm tanks must be equipped with an approved recording thermometer device			
480.75 (a) (2)	9. The recording thermometer sensor bulb shall be located as to record the temperature of the milk in the tank before the milk reaches 10% of the tank volume.			
480.7 (d)	10. Sanitary Caps must be provided for all tank outlets and valves			
33524	11. All farm tank openings must be tightly sealed			
480.7 (e)	12. Sanitary milk pumps provided by the dairy must be protected at all times			
480.7 (g)	13. Tank must be constructed of acceptable materials and in such a manner that it may be cleaned, sterilized, and drained. The measuring device must be made of stainless steel			
480.7 (g)	14. All valves and fittings of farm tanks must be easily disassembled for cleaning.			
480.7	15. Sufficient light to be properly protected; must be available to assure cleaning of the interior and exterior of the farm tank.			
480.6	16. No equipment shall be so located as to interfere with cleaning under, over, or around the equipment.			

Dairy Inspector: _____ Date: _____